



REVISIONS			
REV	DESCRIPTION	DATE:	BY:
3	ADDED VARIOUS NOTES.	03-10-14	WW

QTY	ITEM	PART #	DESCRIPTION	LOCATION
1	A	WHCE200	2" FNPT CPLG (MIXER)	CAP
1	B	WHCE200	2" FNPT CPLG (DRAIN)	CENTER BOTTOM
1	C	WHCE200	2" FNPT CPLG (SPARE)	TOP
1	D	WHCE075	.75" FNPT CPLG (VENT)	TOP

NOTES:

1-TDC00125A; CYL, DOME-TOP, DOME- BOTTOM, 34" DIA X 44" HT, 5/16" WALL PREMIUM GRADE FDA APPROVED HIGH DENSITY POLYETHYLENE, W/ PUSH/ PULL HANDLES AND INTEGRATED VFD MOUNT.

2-SCREW CAP, 6", VITON GASKET.

3-MOLDED PEDESTAL, LINEAR POLYETHYLENE, BLUE.

4-MOBILE DOLLY, FABRICATED HDPE W/ 4" CASTERS, ALL SWIVEL W/ TOTAL LOCKING BRAKES.

5-MIXER MODEL; WMP-TCM-1XT (1.5 air motor) with; 316SS SHAFT
316SS 5" PROP, SET SCREWED
MOTOR OPTIONS; AIR OR ELECTRIC, 0.25 - 3.0 HP
ANY CUSTOM CONFIGURATION AVAILABLE.

6-UNIT SUPPLIED WITH ;
2" PVC TRUE UNION BALL VALVE = 1PC
2" PVC 90° ELBOW T X T = 1 PC
2" PVC NIPPLE, THREAD/ CLOSE = 2 PCS
2" PVC THREADED HEX PLUG = 2 PCS
3/4" PVC THREADED HEX PLUG = 1 PC

7-DESIGN BRIM FULL VOLUME; 125 GAL/ 473.13 LITERS

APPROVED: _____ DATE: _____

COMMENTS:

125 GAL MIX, INDUSTRIAL

DRAWN BY: W.W.	Rev 3
DATE: 03-10-2014	SCALE: NTS
	DWG. NO.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES: X.X = ± 1.2"
X.XX = ± 0.125"
X.XXX = ± 0.063"